

ENGLISH

MONTI

YOUR SURFACE - OUR PASSION



BRISTLE BLASTER®

QUALITY MADE IN GERMANY SINCE 1987

THE KEYFEATURES OF BRISTLE BLASTING

What is the Bristle Blasting process?


Bristle Blasting is a new process that uses a specially designed rotary bristle tool for achieving both corrosion removal and an anchor profile.

How does the tool perform blasting operations?

The bristle tips are designed to strike the corroded surface with kinetic energy that is equivalent to standard processes that use grit blast media. Immediately after the bristle tips strike the surface, they retract (“rebound”) from the surface, which results in both corrosion removal and micro-indentation that exposes fresh surface.

Consequently, surfaces that have been treated by Bristle Blasting have a texture and visual cleanliness that mimics those obtained by traditional grit blasting processes.

The bristles are obstructed (creating a tension), accelerated (released from the Accelerator Bar), impact the surface, and retract from the surface




Sequences from the high-speed-video, recorded with a frame rate of 30,000 frames/sec
Hub speed: 2,500 rpm
Impact duration: 0.0003 sec


Advantages

- visual cleanliness as achieved by grit blasting (near white metal or SSPC-SP 10 or SA 2.5)
- roughness capability from 40-120 μm R_z (1.6-4.7 mils)
- hand held power tool, easy to operate and to transport (weight of Bristle Blaster[®] Pneumatic approx. 1.2 kg / 2.6 lbs)
- no complex equipment, machinery or work preparation required – only compressed air or electric power supply
- ATEX approved for the use in Zone 1 – potentially explosive atmospheres (for Bristle Blaster[®] Pneumatic)
- grit free process – no additional waste production
- no need for housing installations, no reprocessing or disposal of grit media needed
- ideal for spot-repair and touch-up jobs

Corroded surface before and after treatment by Bristle Blaster[®]



Scanning electron micrograph of bristle blast surface



20x

100x



Bristle Blaster® Pneumatic

| Technical data: | |
|---------------------------------|-------------------------|
| Weight: | 1.1 kg 2.4 lbs |
| Air pressure connection thread: | Rp 1/4" |
| Required hose diameter: | 9.5 mm 3/8" |
| Rotational speed: | 3500 min ⁻¹ |
| Required flow pressure: | 6.2 bar 90 psi |
| Average air consumption: | 0.5 m ³ /min |
| Vibration: | 2 m/sec ² |
| Sound pressure level: | 83 dB(A) |

Bristle Blaster® Electric

| Technical data: | |
|-----------------------|--------------------------------|
| Weight: | 2.2 kg 4.8 lbs |
| Output: | 700 W |
| Voltage: | 230 V (±10 %) 120 V (±10 %) |
| Rotational speed: | 3200 min ⁻¹ |
| Vibration: | 2.8 m/sec ² |
| Sound pressure level: | 83 dB(A) |

Ex II 2G c IIA T4 X

Bristle Blaster® Pneumatic was approved by ATEX for the use in Zone 1 – potentially explosive atmospheres

PERFORMANCE OF THE BRISTLE BLASTER® TECHNOLOGIE

Corrosion, Mill Scale, and Coating Removal

Restores surface to near white metal visual standard (or SA 2.5, NACE 2 or SSP-SP-10)

Surface Texture / Anchor Profile

Roughness capability from 40-120 µm R_z (1.6-4.7 mils) – depending on treated material. Also on weld seams

Eco-friendly

„Green“ surface treatment, does not use or produce hazardous materials

Improved Integrity of Treated Surface

Generates compressive residual stress along the treated surface for crack growth resistance, improved fatigue life, and improved corrosion resistance

Negligible Heat Generation

Surface free of thermal damage/heat marking

Simple / Economical

Eliminates the need for complex and costly abrasive blast equipment



Bristle Blaster® Set Pneumatic:

consisting of:

- drive unit Bristle Blaster® Pneumatic with air cooling, noise reduction, dust exhaust, special gear reduction
- Adaptor Systems for 23mm- and 11mm-belts
- Accelerator Bars for 23mm- and 11mm-belts
- Air Pressure Regulators for 23mm- and 11mm-belts, with couplings and nipples
- 5 Bristle Blaster® Belts, 23 mm
- 5 Bristle Blaster® Belts, 11 mm
- packed in a blow mould case

Art.No. SP-647-BMC

As Set for stainless steel or aluminum surface preparation:

incl. stainless steel Belts and stainless steel Accelerator Bars

Art.No. SP-649-BMC



Bristle Blaster® Set Electric:

consisting of:

- drive unit Bristle Blaster® 230V resp. 120V with special gear reduction
- Adaptor System for 23mm-belts
- Accelerator Bar for 23mm-belts
- 10 Bristle Blaster® Belts, 23mm
- packed in a blow mould case

230V Art.No. SE-677-BMC
120V Art.No. SE-667-BMC

As Set for stainless steel or aluminum surface preparation:

incl. stainless steel Belts and stainless steel Accelerator Bar

230V Art.No. SE-678-BMC
120V Art.No. SE-668-BMC



Bristle Blaster® Belts, carbon spring steel

bristles: 0.7 mm carbon spring steel, angled, ground tips

ring color: red

23 mm width:

Art.No. BB-033-10

11 mm width:

Art.No. BB-034-10

(10 pack)



Bristle Blaster® Belts, stainless steel

bristles: 0.7 mm stainless steel, angled, ground tips

ring color: white

23 mm width:

Art.No. BB-102-10

11 mm width:

Art.No. BB-103-10

(10 pack)



Adaptor Systems

for 23mm-belts:

Art.No. AS-009

for 11mm-belts:

Art.No. AS-012



Quick Add®

for 23mm-belts

AS-015-23

for 11mm-belts

AS-015-11



Swivel Connector

for air supply

Art.No. ZU-073



Air Pressure Regulators

for 23mm-belts **ZU-071**

for 11mm-belts **ZU-070**

MONTI - Werkzeuge GmbH
 Germany
 T +49 (0) 2242 9090 630
 www.monti.de
 info@monti.de

MONTI - Tools Inc.
 USA
 T +1 832 623 7970
 www.monti-tools.com
 info@monti-tools.com

MONTI

YOUR SURFACE - OUR PASSION

Art.Nr.: P-033-EN (08/2016)